

## LCD Programmable controller (with timing function)

### Features:

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Auto-controller of fan speed to prevent damage to the samples.
- Large LCD screen to display more data at same time.
- Self-check function easy to identify problems.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.
- Programmable controller: 7 periods 63 steps, 0 ~ 5999mins for each periods, fan speed 0 to 100% adjustable.
- Independent audible and visible temperature-limiting alarm system ensures experiments run safely.
- RS485 connector can connect computer and printer to record the parameters and the variations of temperature.(Option)



### Specifications

Model	BPH-9042	BPH-9082	BPH-9162	BPH-9272	BPH-9402
Electrical Requirement	220V 50HZ				
Controller	LCD Programmable controller				
Temperature Range	RT+5°C ~80°C				
Display Resolution	0.1°C				
Temperature Stability	±0.2°C				
Temperature Uniformity	±1.5(at 37°C )				
Ambient Temperature	+5~35°C				
Power Consumption	250W	250W	500W	600W	1200W
Interior Dimension(W×D×H)mm	350×300×400	400×320×550	500×380×750	600×450×900	1000×510×800
Exterior Dimension(W×D×H)mm	505×635×600	550×660×750	655×715×980	755×785×1130	1140×850×1080
Shelves	2(pcs)				
Timing Range	0~5999min				
Remark	Model BPH-9042 without observation window				

### Options:

- Printer



- USB data collect



- RS485 connector



- UV Sterilizer

