

## Technical Advantage Performance and Features

- Temperature Range: Amb+5°C ~65°C .
- P.I.D temperature controller provides accurate and reliable temperature control.
- Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage.
- Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed.

### Convenience

- Volume(10L~210L).
- Inner chamber is made from corrosion-resistant mirror stainless steel.
- Round curved inner angle is easy to clean.
- Anti-skid shelf design, easy to operate by single hand.

### Safety

- Auto Start Feature after power loss/return.
- Temperature deviation alarm.
- Over current protection alarm.
- Independent Over-temperature protection meets DIN 12880 International standard requirements provides you double protection.(Option)



## Specifications

Model	DHP-9011	DHP-9031	DHP-9051	DHP-9121	DHP-9211
Electrical Requirement	220V 50Hz				
Temperature Range	Amb+5~65°C				
Display Resolution	0.1°C				
Ambient Temperature	+5~35°C				
Power Consumption	85W	125 W	250 W	550W	900W
Inner glass door	None		Has		
Viewing window	Has		None		
Chamber Volume	16L	35L	50L	115L	220L
Interior Dimension (WxDxH ,mm)	270×260×232	360×325×300	400×330×380	520×450×495	650×500×680
Exterior Dimension (WxDxH, mm)	507×397×347	597×464×417	665×667×600	785×587×715	915×657×870
Shelves	2PCS			3PCS	

## Options

- Intelligent programmable temperature controller

- Independent temperature-limiting Alarm system



- RS485 connector

